

Sento Floor-Mounted Tub Filler

- Floor-mount installation
- Aerated spout flow rate ~8 gpm @ 45 psi
- Handshower flow rate ≤ 1.5 max gpm
- 7-7/8" spout reach
- 30" - 34-5/16" approximate height
- Includes handshower with 59" spiral flexible hose (PVD finishes use 59" flex hose)
- Optional in-line pressure balancing valve

- ADA

- Gold 24K
- Gebürstetes Gold 24K
- Gebürstetes Messing PVD®
- Schwarz_Architectural Black™
- Gebürstetes Onyx PVD®
- Rosé-Gold / Gebürstetes Kupfer PVD®
- Gunmetal PVD®
- Gunmetal gehämmert
- Matt schwarz
- Olivebraun
- Onyx PVD®
- Poliertes Messing PVD®
- Poliertes Chrom
- Poliertes Nickel
- Rosé-Gold / Poliertes Kupfer PVD®
- Seideglänzendes Nickel Steelnox®
- Rohmessing
- Unbehandeltes gebürstetes Messing
- Weiss

Technical drawing of the 1000 Series Tee fitting, showing side and end views with dimensions in inches and millimeters.

Side View Dimensions:

- Top flange width: 31-1/8" ↔ 34-5/16" (791mm ↔ 871mm)
- Flange thickness: 30-7/16" ↔ 33-5/8" (774mm ↔ 854mm)
- Vertical distance from top flange to centerline: 8-1/16" (200mm)
- Vertical distance from centerline to bottom flange: 7-7/8" (200mm)
- Horizontal distance from centerline to vertical branch centerline: 4-1/4" (108mm)
- Vertical branch diameter: 8-1/8" (206mm)
- Vertical branch length: 4-1/16" (119mm)
- Vertical branch diameter: 2-15/16" (74mm)
- Horizontal distance from vertical branch centerline to end of fitting: 4-1/8" (104mm)

End View Dimensions:

- Flange outer diameter: 4-1/16" (119mm)
- Flange thickness: 1/2" (12mm)
- Vertical branch diameter: 2-15/16" (74mm)
- Vertical branch length: 4-1/16" (119mm)
- Vertical branch diameter: 8-1/8" (206mm)
- Vertical branch length: 4-1/8" (104mm)